


▶ Insulated Conduit Bushing

Standard: UL 514B and C22.2 No. 18.3-12

Material: Zinc

Application: for use with locknut to terminate Rigid or IMC conduit to a box or enclosure




EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
Q11	1/2"	150	1500	1.051	0.788
Q12	3/4"	100	1000	1.325	0.984
Q13	1"	50	500	1.585	1.260
Q14	1-1/4"	50	500	1.950	1.594
Q15	1-1/2"	35	350	2.200	1.831
Q16	2"	20	200	2.695	2.323
Q17	2-1/2"	1	200	3.235	2.776
Q18	3"	1	150	3.885	3.465
Q19	3-1/2"	1	100	4.360	3.895
Q20	4"	1	80	5.010	4.448

▶ Conduit Bushing

Standard: UL 514B and C22.2 No. 18.3-12

Material: Plastic

Application: for use with locknut to terminate Rigid or IMC conduit to a box or enclosure




EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
CPB050	1/2"	100	1000	1.056	0.786
CPB075	3/4"	100	1000	1.318	0.985
CPB100	1"	50	250	1.588	1.260
CPB125	1-1/4"	25	250	1.955	1.594
CPB150	1-1/2"	25	250	2.190	1.831
CPB200	2"	25	125	2.681	2.323
CPB250	2-1/2"	10	50	3.248	2.776
CPB300	3"	10	50	3.871	3.465
CPB350	3-1/2"	10	40	4.365	3.895
CPB400	4"	10	40	5.012	4.449

▶ Insulated Grounding Bushing

Standard: UL 467 and C22.2 No. 41-13

Material: Malleable Iron

Application: for use with locknut to terminate Rigid or IMC conduit to a box or enclosure and quick installation of bonding jumper



EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
Q1-1	1/2"	1	500	1.260	0.787
Q2-2	3/4"	1	500	1.481	0.986
Q3-3	1"	1	300	1.800	1.262
Q4-4	1-1/4"	1	200	2.405	1.595
Q5-5	1-1/2"	1	200	2.500	1.832
Q6-6	2"	1	125	3.028	2.325
Q7-7	2-1/2"	1	100	3.600	2.778
Q8-8	3"	1	60	4.162	3.466
Q9-9	3-1/2"	1	60	4.748	3.898
Q10-10	4"	1	50	5.298	4.450