


▶ Reducing Bushing

Standard: UL 514B and C22.2 No. 18.3-12

Material: Steel

Application: for reducing the threaded opening in conduit bodies or any female threaded fitting




EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
RDB01	3/4"*1/2"	100	1000	0.921	0.645
RDB02	1"*1/2"	50	500	1.124	0.715
RDB03	1"*3/4"	50	500	1.124	0.715
RDB04	1-1/4"*1/2"	1	210	1.472	0.818
RDB05	1-1/4"*3/4"	1	210	1.472	0.818
RDB06	1-1/4"*1"	1	210	1.472	0.818
RDB07	1-1/2"*1/2"	1	120	1.700	0.850
RDB08	1-1/2"*3/4"	1	120	1.700	0.850
RDB09	1-1/2"*1"	1	120	1.700	0.850
RDB10	1-1/2"*1-1/4"	1	120	1.700	0.850
RDB11	2"*1/2"	1	75	2.228	0.972
RDB12	2"*3/4"	1	75	2.228	0.972
RDB13	2"*1"	1	75	2.228	0.972
RDB14	2"*1-1/4"	1	75	2.228	0.972
RDB15	2"*1-1/2"	1	75	2.228	0.972

▶ Bushed Nipple

Standard: UL 514B and C22.2 No. 18.3-12

Material: Zinc

Application: for use to connect box to conduit coupling, or box to box




EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
BNP01	1/2"	100	1000	1.025	0.585
BNP02	3/4"	50	500	1.300	0.614
BNP03	1"	25	250	1.616	0.654
BNP04	1-1/4"	1	250	1.978	0.810
BNP05	1-1/2"	1	100	2.410	0.835
BNP06	2"	1	50	2.945	0.888

▶ Conduit Nipple - Close

Standard: UL 1242, ANSI C80.6

Material: Steel

Application: when screwed tightly between two female fittings, very little of the nipple remains exposed.



EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
AT01	1/2"	100	1000	1.532	0.785
AT02	3/4"	50	500	1.571	0.982
AT03	1"	30	300	1.890	1.258
AT04	1-1/4"	1	200	2.045	1.593
AT05	1-1/2"	1	120	2.205	1.831
AT06	2"	1	60	2.360	2.322