

## ▶ Liquid Tight Connector - 45°

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** Malleable Iron

**Application:** for use to bond liquid tight conduit to a box or enclosure




EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
310	3/8"	1	200	1.000	1.381
311	1/2"	1	250	1.055	1.381
312	3/4"	1	125	1.188	1.500
313	1"	1	100	1.382	1.690
314	1-1/4"	1	50	1.628	1.939
315	1-1/2"	1	25	1.810	2.252
316	2"	1	25	1.939	2.750

## ▶ Liquid Tight Connector 90°

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** Malleable Iron

**Application:** for use to bond liquid tight conduit to a box or enclosure



EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
320	3/8"	1	200	1.805	1.305
321	1/2"	1	250	1.878	1.398
322	3/4"	1	150	2.058	1.625
323	1"	1	100	2.252	2.058
324	1-1/4"	1	50	2.751	2.125
325	1-1/2"	1	50	3.125	2.700
326	2"	1	25	3.880	2.950

## ▶ Non-Metallic Liquid Tight Connector - Straight

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** PVC

**Application:** for use to bond non-metallic liquid tight conduit to a box or enclosure




EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
469P	3/8"	25	100	2.000	1.400
470P	1/2"	25	100	2.000	1.400
471P	3/4"	10	100	2.200	1.700
472P	1"	5	50	2.280	2.000
473P	1-1/4"	5	25	2.440	2.400
474P	1-1/2"	2	10	2.700	2.670
475P	2"	2	10	2.990	3.280

## ▶ Non-Metallic Liquid Tight Connector 90°

**Standard:** UL 514B and C22.2 No. 18.3-12

**Material:** PVC

**Application:** for use to bond non-metallic liquid tight conduit to a box or enclosure



EVT#	Trade Size	Shelf QTY	Master QTY	Dim A (inch)	Dim B (inch)
489P	3/8"	10	100	2.120	3.120
490P	1/2"	10	100	2.120	3.120
491P	3/4"	10	100	2.500	3.600
492P	1"	5	50	3.125	4.125
493P	1-1/4"	5	25	4.450	5.200
494P	1-1/2"	2	10	4.750	5.200
495P	2"	2	10	5.420	5.800