

▶ Octagonal Box 4"

Standard: UL 514A and CSA C22.2. No. 18.1-13

Material: Steel

Application: used for switches, outlets or used as a small junction box



EVT#	Depth	Thickness(mm)	Knockouts	Capacity	Master QTY
OB01	1-1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"	15.8 Cu. In.	50
OB02	1-1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	3/4"	15.8 Cu. In.	50
OB03	1-1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"&3/4"	15.8 Cu. In.	50
OB11	1-7/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"	19.8 Cu. In.	50
OB12	1-7/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	3/4"	19.8 Cu. In.	50
OB13	1-7/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"&3/4"	19.8 Cu. In.	50
OB16	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"	22.5 Cu. In.	50
OB17	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	3/4"	22.5 Cu. In.	50
OB18	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"&3/4"	22.5 Cu. In.	50
OB19	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1"	22.5 Cu. In.	50

▶ Octagonal Box 4" Extension Type

Standard: UL 514A and CSA C22.2. No. 18.1-13

Material: Steel

Application: for use to extend the depth of octagonal steel box 4"



EVT#	Depth	Thickness(mm)	Knockouts	Capacity	Master QTY
OB21	1-1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"	15.8 Cu. In.	50
OB22	1-1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	3/4"	15.8 Cu. In.	50
OB23	1-1/2"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"&3/4"	15.8 Cu. In.	50
OB26	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"	22.5 Cu. In.	50
OB27	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	3/4"	22.5 Cu. In.	50
OB28	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"&3/4"	22.5 Cu. In.	50
OB29	2-1/8"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1"	22.5 Cu. In.	50

▶ Octagonal Box with 8-Side-KO

Standard: UL 514A and CSA C22.2. No. 18.1-13

Material: Steel

Application: used for switches, outlets or used as a small junction box



EVT#	Depth	Thickness(mm)	Knockouts	Capacity	Master QTY
OB08	1-3/4"	0.8 / 1.0 / 1.2 / 1.5 / 1.6	1/2"&3/4"	23.3 Cu. In.	50